

 <b>RFMORECOM.</b> Korea	<h1>Specification</h1>	<i>Item</i>	<i>REV</i>
		<b>BPF</b>	<b>00</b>

Part no : RMC2595B190M02

**1. FEATURES**

- HIGH PERFORMANCE
- HIGH RELIABILITY
- SMD TYPE
- RoHS Compliant

**2. Electrical Specification**

ITEM	Specification	Notes
<b>3-1. Frequency Range</b>	2500MHz ~ 2690MHz	
<b>3-2. Insertion Loss</b>	0.6dB Typical 0.8dB Max(Temp.)	
<b>3-3. Ripple</b>	0.7dB Max	
<b>3-4. Return Loss</b>	18dB Min	
<b>3-5. Attenuation</b>	35dBc Min @2690MHz+20MHz...50MHz 65dBc Min @2690MHz+50MHz...200MHz 35dBc Min @2500MHz-20MHz...50MHz 65dBc Min @2500MHz-50MHz...200MHz 75dBc Min @400MHz...2200MHz	
<b>3-6. Sniffer(MON)</b>	-30dB 1.0dB	
<b>3-7. Power</b>	50W CW Max	
<b>3-8. Input/Output Impedance</b>	50 Ohm nominal	



### 3. Mechanical Specification

